



SIMPLE KEYLESS ACCESS



The KL1000 is a compact digital lock ideal for replacing keyed cam locks commonly supplied on a wide range of lockers, cabinets and cupboards.

This neat lock is easy to fit, taking just a few minutes to remove the existing cam lock and making an additional top fixing. KL1000 can also be fitted to a locker or cabinet that does not have an existing locking device - just drill another hole. Once in place the lock will perform up to 15,000 openings on just two AAA batteries. Access control without the need for keys.



Easy to
install



On the door
programming



Two year
limited warranty*



Private and
Public Functions

FEATURES

- 11 button keypad
- 8 digit Master and Sub-Master Code
- 4 digit User Code
- 6 digit Technician Code
- Left hand and right hand versions available
- Up to 15,000 operations from 2 x AAA batteries (supplied)
- Battery override
- Slam latch accessory available
- IP55 rated when fitted with gasket
- All parts / fasteners / templates included



FUNCTIONS




Private Function

This is the default function and is already pre-programmed in new locks. This function is used where the same code will be repeatedly used, e.g. an employee with the same locker/drawer in the workplace.



Public Function

In this function the KitLock operates with a single User Code. The user enters a personal four digit code, this locks the lock. The same code is entered once only to open the lock before automatically being erased and ready for the next user. This function is used for short term, multiple occupancy applications, e.g. hot desking in an office or a locker in a sports club.



LED indicators for entry / no entry / low battery

Easy touch buttons

Vertical, left hand or right hand models available

Swivel handle reveals # button used for programming

PRODUCT DIMENSIONS



Code Management

KL1000 has four code levels available:

- 8 digit Master Code
- 8 digit Sub-Master Code
- 4 digit User Code
- 6 digit Technician Code


The KitLock is supplied with two factory set codes:

- Master Code
- User Code

Before installing, change the Master and User Code by following the Programming and Operating Instructions.

Easy Installation

Everything you need is included to ensure a quick and easy installation.



TECHNICAL SPECIFICATIONS

FEATURE	DESCRIPTION
Operations	Up to 15,000 opening per 2 x 1.5 AAA batteries
Battery Override	A 9 volt battery can be placed against external contacts
Low Battery Warning	Red LED will flash on opening to indicate low battery
Functions	Private and Public
Buttons	11 individual round buttons
Material	Zinc Alloy
Finish Color	Silver gray and black as standard
Door Thickness	Ready to fit doors up to 1" (25mm)
Memory	Non-volatile memory will be retained
Installation	Easy to install and program
Install Options	Vertical, right hand and left hand models
IP55 Rated	When used with rubber gasket (available separately)
Crank Cam	Backset: 1 7/16" (37mm) Overall Length: 1 3/4" (45mm)
Flat Cam	Backset: 1 1/4" (32mm) Overall Length: 1 9/16" (40mm)
Slam Latch	Retrofit to existing KL1000 locks or purchase for new locks. Easy shutting.

Note: Not suitable for Chlorine environments.



Scan to shop!

www.kitlock.com

